

IAPMO OCEANIA

7-11 Fullard Road, Narre Warren, Victoria 3805, Australia /info@lapmooceania.org



IAPMO oceania is a product certification body which inspects and arranges for the independent laboratory testing of samples taken from the manufacturer's stock or from the market or a combination of both, to verify compliance of the requirements of applicable Standards and Specifications. This activity is coupled with periodic surveillance of the certified product taken from the market place or the manufacturer's factory. This certification is subject to the conditions set forth in the characteristics below and is not to be construed as any recommendation, assurance or guarantee by IAPMO oceania of the product acceptance by Authorities Having Jurisdiction.

GASMARK CERTIFICATE

IAPMO Oceania hereby grants to:

Escea Ltd

17 Canforth Street, Green Island, Dunedin, Otago 9018 New Zealand

Email: australia@escea.com.au

the right to use the GasMark in accordance with IAPMO oceania Pty Ltd 'Mark Rules' on the product as described in the attached GasMark Schedule. The Certificate is granted subject to IAPMO oceania Pty Ltd 'Governance Rules'.

Evaluated to:

AS/NZS 5263.1.3:2021 Amdt 1

Gas space heating appliances

AS/NZS 5263.0:2023

Miscellaneous

Manufacturer:

Refer to Certificate Holder

Certificate No.: GMK10520

First Certified: 22 May 2018

Certification Date: 12 Aug 2025

Expiry Date: 21 May 2028

A handwritten signature in black ink, reading "David Viola". The signature is fluid and cursive, with the first name "David" and last name "Viola" clearly distinguishable.

David Viola

Chief Executive Officer of the IAPMO Group

This GasMark certification is for the period indicated herein and is void after the date shown above. Any change in material, manufacturing process, marking or design without having first obtained the approval of IAPMO R&T Oceania, or any evidence of non-compliance with applicable Standards, Specifications or of inferior workmanship, may be deemed sufficient cause for revocation of this certification. Reproduction of or reference to this certificate for advertising purposes may be made only by specific written permission of IAPMO oceania. Any alteration of this certificate could be grounds for revocation of this certification.



GASMARK SCHEDULE



Certificate Holder

Escea Ltd

A.B.N.:

17 Canforth Street, Green Island, Dunedin, Otago 9018 New Zealand

Manufacturer

Refer to Certificate Holder

Standards

AS/NZS 5263.1.3:2021

Gas space heating appliances

AS/NZS 5263.1.3:2021 Amdt 1

Gas space heating appliances

AS/NZS 5263.0:2023

Miscellaneous

Certificate No. GMK10520

Certification Date: 12 Aug 2025

Expiry Date: 21 May 2028

First Certified: 22 May 2018

Brand Name	Model ID	Gas Type	Product Description	Input	Flue	Star Rating	Star Shading	Features
MODE	KS1150 Single-Double 850	NG	Room sealed flame effect heater	41MJ/h	Remote power flue up to 40m, optional side exhaust port for horizontal power flue	3.4	103	Glass primary guard; fuelbed media: logs & flakes/embers; coals; crystalight/gems; crystalight/gems & driftwood; woodland log; redwood elevation; Australian Oak/Splitwood and embers; Driftwood, embers and shale
MODE	KS1150 Single-Double 850	Propane	Room sealed flame effect heater	41MJ/h	Remote power flue up to 40m, optional side exhaust port for horizontal power flue	3.4	103	Glass primary guard; fuelbed media: logs & flakes/embers; coals; crystalight/gems; crystalight/gems & driftwood; woodland log; redwood elevation; Australian Oak/Splitwood and embers; Driftwood, embers and shale
MODE	KS1150 Single-Double 850	ULPG	Room sealed flame effect heater	41MJ/h	Remote power flue up to 40m, optional side exhaust port for horizontal power flue	3.4	103	Glass primary guard; fuelbed media: logs & flakes/embers; coals; crystalight/gems; crystalight/gems & driftwood; woodland log; redwood elevation; Australian Oak/Splitwood and embers; Driftwood, embers and shale
MODE	KS1150 Peninsula/Corner 400	NG	Room sealed flame effect heater	33MJ/h	Remote power flue up to 40m, optional side exhaust port for horizontal power flue	3.4	101	Glass primary guard; fuelbed media: logs & flakes/embers; coals; crystalight/gems; crystalight/gems & driftwood; woodland log; Australian Oak/Splitwood and embers; Driftwood, embers and shale
MODE	KS1150 Peninsula/Corner 400	Propane	Room sealed flame effect heater	33MJ/h	Remote power flue up to 40m, optional side exhaust port for horizontal power flue	3.4	101	Glass primary guard; fuelbed media: logs & flakes/embers; coals; crystalight/gems; crystalight/gems & driftwood; woodland log; Australian Oak/Splitwood and embers; Driftwood, embers and shale
MODE	KS1150 Peninsula/Corner 400	ULPG	Room sealed flame effect heater	33MJ/h	Remote power flue up to 40m, optional side exhaust port for horizontal power flue	3.4	101	Glass primary guard; fuelbed media: logs & flakes/embers; coals; crystalight/gems; crystalight/gems & driftwood; woodland log; Australian Oak/Splitwood and embers; Driftwood, embers and shale
MODE	KS1460 Single/Double/Peninsula/Corner	NG	Room sealed flame effect heater	41MJ/h	Remote power flue up to 40m, optional side exhaust port for horizontal power flue	3.4	103	Glass primary guard; fuelbed media: glass gems; riverstone and shale; redwood logs and embers; Kitset Wall Unit (KWU) for Peninsula/Corner
MODE	KS1460 Single/Double/Peninsula/Corner	Propane	Room sealed flame effect heater	38MJ/h	Remote power flue up to 40m, optional side exhaust port for horizontal power flue	3.4	103	Glass primary guard; fuelbed media: glass gems; riverstone and shale; redwood logs and embers; Kitset Wall Unit (KWU) for Peninsula/Corner

Brand Name	Model ID	Gas Type	Product Description	Input	Flue	Star Rating	Star Shading	Features
MODE	KS1460 Single/Double/Peninsula/Corner	ULPG	Room sealed flame effect heater	38MJ/h	Remote power flue up to 40m, optional side exhaust port for horizontal power flue	3.4	103	Glass primary guard; fuelbed media: glass gems; riverstone and shale; redwood logs and embers; Kitset Wall Unit (KWU) for Peninsula/Corner
Escea	DN1150 Peninsula/Corner 400	NG	Room sealed flame effect heater	33MJ/h	Remote power flue up to 40m, optional side exhaust port for horizontal power flue	3.4	101	Glass primary guard; fuelbed media: logs & flakes/embers; coals; crystalight/gems; crystalight/gems & driftwood; woodland log; splitwood and embers; driftwood, embers and shale
Escea	DN1150 Peninsula/Corner 400	Propane	Room sealed flame effect heater	33MJ/h	Remote power flue up to 40m, optional side exhaust port for horizontal power flue	3.4	101	Glass primary guard; fuelbed media: logs & flakes/embers; coals; crystalight/gems; crystalight/gems & driftwood; woodland log; splitwood and embers; driftwood, embers and shale
Escea	DN1150 Peninsula/Corner 400	ULPG	Room sealed flame effect heater	33MJ/h	Remote power flue up to 40m, optional side exhaust port for horizontal power flue	3.4	101	Glass primary guard; fuelbed media: logs & flakes/embers; coals; crystalight/gems; crystalight/gems & driftwood; woodland log; splitwood and embers; driftwood, embers and shale

END RECORD

END RECORD



David Viola
Chief Executive Officer of the IAPMO Group